



Easy, Elegant Design Fits Your Lifestyle

Our LT heaters are powerful, efficient and easy to operate. And inside the incredibly reliable LT heaters, you'll find plenty of features to warm up to:

- ▶ Automatic pool-to-spa switching
- ▶ Fan-assisted controlled combustion for consistent efficiency—up to 83%
- ▶ Corrosion resistant polymer headers for long term reliability
- ▶ Meets all air quality standards (Low NOx)
- ▶ Contemporary design blends into any backyard landscape

POOL-TO-SPA SWITCHING



The LT heater is automation ready with convenient pool to spa switching, eliminating the drudgery of manually turning valves to operate the spa.

DUAL ELECTRONIC THERMOSTAT



Dual set points provide convenient pool and spa temperature settings. LED indicators give easy to understand diagnostic information.

REMOTE CONTROL



With the addition of the EZ Wireless Remote Control, you can operate pool and spa functions without trips to the equipment area.



Powerful, Efficient and Automation-Ready

LT Heaters



Convenient Controls

and dual electronic thermostat are key elements in your AquaLink® RS controlled pool and spa environment. The LT includes automation-ready features to provide convenient pool-to-spa switching.



LT PERFORMANCE CHARTS

The Pool Sizing Guide below shows the maximum pool surface area LT models 250 and 400 will heat based on the Temperature Difference* between the air temperature during the coldest month the pool is used and the desired pool temperature. Figures are based on average wind conditions and average pool depth.

POOL SIZING GUIDE

Model	250		400	
Temp Difference*	Maximum Area Heater (width x length)			
	0 Wind	3 1/2 MPH	0 Wind	3 1/2 MPH
15°F	1750	1300	2800	2100
20°F	1300	1000	2100	1600
25°F	1050	800	1700	1280
30°F	850	650	1400	1050
35°F	750	570	1200	900

The Spa Sizing Guide below details the time required for each model to raise spa temperature by 30°F.

SPA SIZING GUIDE

Model	250	400
Spa Size	Time Required to Raise Temp 30°	
200 Gallons	15 Minutes	10 Minutes
400 Gallons	30 Minutes	20 Minutes
600 Gallons	45 Minutes	30 Minutes
800 Gallons	60 Minutes	45 Minutes
1000 Gallons	75 Minutes	50 Minutes

Specifications:

Model	"A" Width	Height	Depth	VENT	Shipping Weight	Heater Weight
250	28 1/4"	30 7/8"	27 1/8"	7.0"	237 lbs.	170 lbs.
400	34 1/4"	30 7/8"	27 1/8"	9.0"	308 lbs.	236 lbs.

See your Jandy Sales Representative for more information!



ALL JANDY PRODUCTS WORK SEAMLESSLY TOGETHER

Jandy Control Systems manage our complete line of technologically advanced products.



Pumps • Filters • Heaters • Air Energy Heat Pumps
Controls • Lights • Water Purification Systems • Valves
Water Features • Cleaners • Accessories

